

Cassette 360°

15 références

2,2 – 16 kW

Diffusion 360°

R410A

Façade décorative **950 × 950 × 65 mm** (toutes références) · raccordement Flare · pompe de relevage intégrée.

GAMME COMPLÈTE — 15 PUISSANCES

Référence	Froid kW	Chaud kW	Débit G.V. m³/h	Sonore dB(A)	Ø Gaz pouce	Ø Liq. pouce	Corps L×P×H mm	Poids kg
IGCLC22VD	2,2	2,5	800	32	3/8"	1/4"	840×840×200	19
IGCLC28VD	2,8	3,2	800	32	3/8"	1/4"	840×840×200	19
IGCLC36VD	3,6	4	800	32	1/2"	1/4"	840×840×200	19
IGCLC45VD	4,5	5	900	35	1/2"	1/4"	840×840×200	19
IGCLC50VD	5	5,6	900	35	1/2"	1/4"	840×840×200	19
IGCLC56VD	5,6	6,3	1100	37	5/8"	3/8"	840×840×200	21
IGCLC63VD	6,3	7,1	1100	37	5/8"	3/8"	840×840×200	21
IGCLC71VD	7,1	8	1100	37	5/8"	3/8"	840×840×200	21
IGCLC80VD	8	9	1400	40	5/8"	3/8"	840×840×240	22,5
IGCLC90VD	9	10	1400	40	5/8"	3/8"	840×840×240	22,5
IGCLC100VD	10	11,2	1550	43	5/8"	3/8"	840×840×240	22,5
IGCLC112VD	11,2	12,5	1550	43	5/8"	3/8"	840×840×240	22,5
IGCLC125VD	12,5	14	1800	46	5/8"	3/8"	840×840×290	25
IGCLC140VD	14	16	1800	46	5/8"	3/8"	840×840×290	25
IGCLC160VD	16	18	2000	51	3/4"	3/8"	840×840×290	36