

Gainable Haute Pression

11 références

2,8 – 28 kW

Haute pression

≤ 200 Pa

Forte pression statique pour longs réseaux gainés • caissons robustes.

SÉRIE D — PRESSION JUSQU'À 200 PA

Référence	Froid kW	Chaud kW	Débit G.V. m³/h	Pression Pa	Sonore dB(A)	Ø Gaz pouce	Ø Liq. pouce	Dim. L×P×H mm
IGCLG28VH	2,8	3,2	550	80	29–35	3/8"	1/4"	700×700×300
IGCLG36VH	3,6	4,0	600	80	30–36	1/2"	1/4"	700×700×300
IGCLG45VH	4,5	5,0	850	80	32–40	1/2"	1/4"	700×700×300
IGCLG71VH	7,1	8,0	1250	200	32–40	5/8"	3/8"	1000×700×300
IGCLG90VH	9,0	10,0	1800	200	34–42	5/8"	3/8"	1400×700×300
IGCLG112VH	11,2	12,5	2000	200	36–43	5/8"	3/8"	1400×700×300
IGCLG140VH	14,0	16,0	2350	200	38–44	5/8"	3/8"	1400×700×300
IGCLG160VH	16,0	18,0	2500	200	40–45	3/4"	3/8"	1400×700×300
IGCLG180VH	18,0	20,0	3000	170	44–49	3/4"	3/8"	1400×700×300

GRAND DÉBIT — SÉRIE A (TRÈS HAUTE PRESSION)

Référence	Froid kW	Chaud kW	Débit G.V. m³/h	Pression Pa	Sonore dB(A)	Ø Gaz pouce	Ø Liq. pouce	Dim. L×P×H mm
IGCLG224VA	22,4	25	4000	≥ 200	54	3/4"	3/8"	1483×791×385
IGCLG280VA	28	31	4400	≥ 200	55	7/8"	3/8"	1686×870×450